


Universe	Sport
Туре	Verticality
Category	Belay Devices And Descenders
Subcategory	Manual Braking Belay/Rappel Devices



REVERSO®

The lightweight REVERSO is a multi-functional belay/rappel device designed for rock climbing, multi-pitch climbing and mountaineering. It can be used to belay a climber and to rappel, and in Reverso mode can be used to belay one or two second climbers. The specific design of the rope channels facilitates smooth rope glide and reduces wear. It is compatible with most rope diameters: single 8.5 to 10.5 mm, half 7.1 to 9.2 mm, and twin 6.9 to 9.2 mm.



Reverso mode for belaying one or two seconds; commonly used on multi-pitch climbs.



V-shaped friction grooves enable controlled braking.



Durable and lightweight.

Short Description

Lightweight multipurpose descender/belay device for use with one or two rope strands, allowing the second to be belayed from the anchor

Selling Points

- Simple to use:
- feeding slack and catching falls are accomplished using standard belay techniques, always keeping a hand on the brake side of the rope
- rope glides smoothly through the device
- V-shaped friction grooves enable controlled braking
- rope installation diagrams for belaying and Reverso mode are engraved on the device
- Multipurpose use for rock climbing, multi-pitch climbing and mountaineering:
- can be used to belay a climber or to rappel on one or two rope strands
- Reverso mode allows the user to belay one or two seconding climbers with assisted braking
- release hole allows the belayer to give slack to a seconding climber using just one carabiner
- · Lightweight and durable:
- compact and ultra-lightweight: only 57 g
- the rounded design of the rope slots limits wear and extends the life of the device
- compatible with most dynamic rope diameters (single 8.5 to 10.5 mm, half 7.1 to 9.2 mm, and twin 6.9 to 9.2 mm)

Specification

- Weight: 57g
- Rope compatibility: single ropes 8.5 to 10.5 mm, half ropes 7.1 to 9.2 mm, and twin ropes 6.9 to 9.2 mm
- Material(s): aluminum frame
- Certification(s): EN 15151-2, UIAA

Specifications by reference

Reference(s)	D017AA00	D017AA01	D017AA02
	C man	earth	
Color(s)	gray	green	red/orange
Made in	GB	GB	GB
Guarantee	3 years	3 years	3 years
Inner Pack Count	1	1	1
Quantity Per Box	18	18	18
EAN	3342540825918	3342540825932	3342540825925

Related product(s)

Am'D Sm'D RUMBA® 8 mm PASO® GUIDE 7.7 mm TANGO® 8.5 mm CORDEX